

Pacific Cycle Co.

260 McEvoy Street • San Jose • CA 95126

Tel 1.888.722.8747 | **Web** www.ridepcc.com | **Email** mark.mcguire@ridepcc.com

2007 BMW F 800 S

MSRP: \$9,950.00* Destination charge (not included in MSRP): \$495



Copyright 2008 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.
 *Actual price determined by dealer. Price excludes taxes, license, options and handling charge.
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Water cooled twin cylinder 4 stroke	Front Wheel	3.50 x 17 cast alloy, five double-spoke
Bore x Stroke	82 mm x 75. mm	Rear Wheel	5.50 x 17 cast alloy, five double-spoke
Displacement	798 cc	Front Tire	120/70 x 17 tubeless
Horsepower	85 bhp @ 8000 rpm	Rear Tire	180/55 x 17 tubeless
Torque	63 lb/ft @ 5800 rpm	Dimensions	
Compression Ratio	12.0 :1	Overall Length	81.9 inches
Valve Gear	DOHC, chain-driven with bucket tappets	Overall Width	33.9 inches
Valves	2 x 32 mm mm intake / 2 x 27,5 mm mm exhaust	Wheelbase	57.7 inches
Valves / Cylinder	4-Four	Ground Clearance	Info. Unavailable
Engine Oil Capacity		Seat Height	32.3 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	63.8 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	3.7 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	401 lbs. excluding options & accessories
Fuel Capacity	4.1 U.S. gallons including 1 gallon reserve	Weight - Wet	450 lbs. excluding options & accessories
Charging System	400 Watts @ 14 Volts	Maximum Load	884 lbs. GVWR
Battery	12 Volts 14 Amps/hour maintenance-free	Standard Colors	
Cooling System	50/50 water/anti-freeze mix, single radiator	Code Price	Description
Drivetrain		695 N / C	Flame red uni
Primary Drive	1:1.930	743 N / C	Lahar gray metallic
Clutch	Multiple plate in oil bath	987 N / C	Sunset yellow uni
1st Gear Ratio	2.46:1	Standard Equipment	
2nd Gear Ratio	1.75:1	Available Equipment	
3rd Gear Ratio	1.38:1	499 \$175.00	Low Suspension including Low Seat (29.9 inches)
4th Gear Ratio	1.17:1	519 \$PKG	Heated Hand Grips
5th Gear Ratio	1.04:1	524 \$PKG	ABS
6th Gear Ratio	0.96:1	530 \$PKG	Tire Pressure Monitoring (TPM)
Final Drive System	Toothed belt drive	539 \$PKG	On Board Computer
Final Drive Ratio	2.35:1	588 \$PKG	White Turn Indicator
Frame and Suspension		603 \$395.00	Anti-Theft Alarm
Frame	Aluminum bridge, engine partly load bearing	774 \$N / C	Dual Bench Seat - Low (31.1 inches)
Front Suspension	43 mm telescopic fork		
Front Travel	5.5 inches		
Rear Suspension	Single cast aluminum swing arm, central spring str		
Rear Travel	5.5 inches		
Brakes			
Brake System	Twin floating disc, four piston fixed calipers		
Front Brakes	Two 4-piston fixed calipers, two floating rotors		
Front Rotor	12.6 inch dual floating rotors		
Rear Brake	Single, two-piston floating caliper		
Rear Rotor	10.4 inch two piston floating caliper		
Actuation Method	Hydraulic, DOT 4 fluid type		